maidaid

C1035WS – Pass through



- 2 Year warranty
- Breaktank as standard
- Internal automatic water softener
- Bright LED display with soft touch controls
- Accurate detergent and rinse aid peristaltic dosing as standard
- Drain pump as standard
- DUAL flow wash pump, reduced power while retaining wash efficiency
- Three selectable cycle options plus special application cycle options
- Cycle times can be tailored to sites requirements
- Selectable energy saving mode
- Selectable thermostop ensures optimum rinse temperatures
- Automatic self-cleaning cycle at end of service
- Surface scrap trays as standard
- Operational self-diagnostics
- Twin traffic light display indicates machine status
- Supplied with one pegged plate, one open and one cutlery basket

In the event of further technical development we reserve the right to alter our design and specification without prior notice

C1035WS – Pass through

	C1035WS
Width - Body Only	635mm
Width - Body and Handle	700mm
Width - Body, Handle & Brackets	725mm
Depth - Body Only	745mm
Depth - Body with Handle Closed	810mm
Depth - Body with Handle Extended Maximum	925mm
Height - Hood Closed(without feet)	1290mm
Height - Hood Open(without feet)	1720mm
Feet Height	165mm to 220mm
Basket size	500 x 500mm
Maximum useable height	380mm
Door Opening	405mm
Number of standard cycles	3
Standard cycle times	70/110/150 seconds - adjustable
Special cycles	Long cycle = 12 minutes
Self-cleaning program	Yes
Water consumption per cycle	2.5 Litres
Wash tank capacity	15 Litres
Power – Single phase options	4.5kW(20Amps)/6.5kW(30Amps)
Power – Three phase	6.5kW(16Amps)
Boiler element	6kW(2/4/6)
Washtank element	2100W
Detergent pump	Peristaltic – precise delivery
Rinse aid pump	Peristaltic – precise delivery
Drain pump	Yes
Drain technology	Partial drain
Breaktank	Yes
Internal automatic water softener	Yes
Water supply pressure	2 to 4 Bar
Water supply temperature	10 to 50 Degrees Celsius
Body construction	Single skin
Door/Hood construction	Single skin
Tank construction	Deep drawn
Hood lift system	Assisted manual operation
Scrap trays	Yes
Wash pump type	Dual flow
Wash pump power	470w
Wash arm - Upper	Composite parallel arms
Wash arm - Lower	Composite parallel arms
Rinse arm - Upper	Combined with wash arms
Rinse arm - Lower	Combined with wash arms
Internal rinse booster pump	Yes
Open cup/glass basket	One
Plate basket	One
User interface (Controls)	Soft touch controls
Hood machine - Interface position (Controls)	Lower Panel